



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series **Professional Distatic**

Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process. Some optional: automatic loading for one or more consecutive cycles, automatic unloading of the residue, automatic sending of the distillate to a remote service tank, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised.



		S 230 Ax / Wx
Electrical protection		AD-T
Installed power		17,0 kW
Dimensions		cm 150 x 180 x 245 H
Weight		Kg. 968

		D 230 Ax / Wx
Electrical protection		Atex II2G IIA T3 to T2
Installed power		17,0 kW
Dimensions		cm 150 x 180 x 245 H
Weight		Kg. 1000



FORMECO

Company Certified UNI EN ISO 9001 : 2000

		S / D 230 Ax / Wx
--	--	--------------------------

Loading capacity		230 litres
Total volume of the boiler		410 litres
Inner diameter of the boiler		510 mm
Condensation unit		Stainless steel AISI 304
Cooling by		Air / Water
Cover opening		manual
Boiler tilting		by geared motor
Suitable for using Rec-Bags		no

Packing list for shipment		
Cardboard on pallet	cm 190 x 200 x 270H	Kg. 1100



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series **Professional DYNAMIC**

Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process. Some optional: automatic loading for one or more consecutive cycles, automatic unloading of the residue, automatic sending of the distillate to a remote service tank, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Boiler equipped with scraping blades.



	SQ 60 A	SQ 60 Ax / Wx
Electrical protection	AD-T	AD-T
Installed power	4,50 kW	4,50 kW
Dimensions	cm 90 x 130 x 165 H	cm 90 x 130 x 165 H
Weight	Kg. 388	Kg. 388

	DQ 60 A	DQ 60 Ax / Wx
Electrical protection	Atex II2G IIA T3 to T2	Atex II2G IIA T3 to T2
Installed power	4,50 kW	4,50 kW
Dimensions	cm 90 x 130 x 165 H	cm 90 x 130 x 165 H
Weight	Kg. 420	Kg. 420



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 60 A	SQ / DQ 60 Ax / Wx
--	---------------------	---------------------------

Loading capacity	60 litres	60 litres
Total volume of the boiler	103 litres	103 litres
Inner diameter of the boiler	400 mm	400 mm
Condensation unit	Copper	Stainless steel AISI 304
Cooling by	Air	Air / Water
Cover opening	manual	manual
Boiler tilting	by geared motor	by geared motor
Suitable for using Rec-Bags	no	no

Packing list for shipment		
Cardboard on pallet	cm 118 x 153 x 197H	Kg. 510



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series *Professional DYNamic*

Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process. Some optional: automatic loading for one or more consecutive cycles, automatic unloading of the residue, automatic sending of the distillate to a remote service tank, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Boiler equipped with scraping blades.



		SQ 120 Ax / Wx
Electrical protection		AD-T
Installed power		10,50 kW
Dimensions		cm 118 x 152 x 203 H
Weight		Kg. 598

		DQ 120 Ax / Wx
Electrical protection		Atex II2G IIA T3 to T2
Installed power		10,50 kW
Dimensions		cm 118 x 152 x 203 H
Weight		Kg. 630



FORMECO

Company Certified UNI EN ISO 9001 : 2000

		SQ / DQ 120 Ax / Wx
--	--	----------------------------

Loading capacity		120 litres
Total volume of the boiler		210 litres
Inner diameter of the boiler		510 mm
Condensation unit		Stainless steel AISI 304
Cooling by		Air / Water
Cover opening		manual
Boiler tilting		by geared motor

Suitable for using Rec-Bags	no	no
-----------------------------	----	----

Packing list for shipment		
Cardboard on pallet	cm 175 x 135 x 217H	Kg. 690



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series *Industrial*

Units composed by a boiler with pneumatic lifting of the cover and a separate box containing the control board electrical box, and all the other components making part of the plant. Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process. Some optional: automatic loading for one or more consecutive cycles, automatic unloading of the residue, automatic sending of the distillate to a remote service tank, regulation the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Boiler equipped with scraping blades.



	SQ 230 Ax / Wx
Electrical protection	AD-T
Installed power	18,0 kW
Dimensions	cm 160 x 306 x 220 H
Weight	Kg. 2118

	DQ 230 Ax / Wx
Electrical protection	Atex II2G IIA T3 to T2
Installed power	18,00 kW
Dimensions	cm 160 x 306 x 220 H
Weight	Kg. 2150



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 230 Ax / Wx
--	----------------------------

Loading capacity	230 litres
Total volume of the boiler	410 litres
Inner diameter of the boiler	700 mm
Condensation unit	Stainless steel AISI 304
Cooling by	Air / Water
Cover opening	pneumatic
Boiler tilting	by geared motor
Suitable for using Rec-Bags	no

Packing list for shipment		
Cardboard on pallet	cm 160 x 306 x 220 H	Kg. 2150



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series *Industrial*

Units composed by a boiler with pneumatic lifting of the cover and a separate box containing the control board electrical box, and all the other components making part of the plant. Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process, automatic loading for one or more consecutive cycles, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Some optional: automatic unloading of the residue, automatic sending of the distillate to a remote service tank. Boiler equipped with scraping blades.



	SQ 300 Ax / Wx
Electrical protection	AD-T
Installed power	16,0 kW
Dimensions	cm 160 x 352 x 332 H
Weight	Kg. 2532

	DQ 300 Ax / Wx
Electrical protection	Atex II2G IIA T3 to T2
Installed power	16,0 kW
Dimensions	cm 160 x 352 x 332 H
Weight	Kg. 2532



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 300 Ax / Wx
--	----------------------------

Loading capacity	300 litres
Total volume of the boiler	530 litres
Inner diameter of the boiler	800 mm
Condensation unit	Stainless steel AISI 304
Cooling by	Air / Water
Cover opening	pneumatic
Boiler tilting	by geared motor
Suitable for using Rec-Bags	no

Packing list for shipment		
Cardboard on pallet	cm 160 x 352 x 332 H	Kg. 2532



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series Industrial

Units composed by a boiler with pneumatic lifting of the cover and a separate box containing the control board electrical box, and all the other components making part of the plant. Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process, automatic loading for one or more consecutive cycles, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Some optional: automatic unloading of the residue, automatic sending of the distillate to a remote service tank. Boiler equipped with scraping blades.



	SQ 600 Ax / Wx
Electrical protection	AD-T
Installed power	32,0 kW
Dimensions	cm 175 x 400 x 375 H
Weight	Kg. 3000

	DQ 600 Ax / Wx
Electrical protection	Atex II2G IIA T3 to T2
Installed power	32,0 kW
Dimensions	cm 175 x 400 x 375 H
Weight	Kg. 3032



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 600 Ax / Wx
--	----------------------------

Loading capacity	600 litres
Total volume of the boiler	965 litres
Inner diameter of the boiler	1000 mm
Condensation unit	Stainless steel AISI 304
Cooling by	Air / Water
Cover opening	pneumatic
Boiler tilting	by geared motor
Suitable for using Rec-Bags	no

Packing list for shipment		
Cardboard on pallet	cm 175 x 400 x 375 H	Kg. 3032



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series Industrial

Units composed by a boiler with pneumatic lifting of the cover and a separate box containing the control board electrical box, and all the other components making part of the plant. Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process, automatic loading for one or more consecutive cycles, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Some optional: automatic unloading of the residue, automatic sending of the distillate to a remote service tank. Boiler equipped with scraping blades.



	SQ 1200 Wx
Electrical protection	AD-T
Installed power	44,0 kW
Dimensions	cm 210 x 440 x 404 H
Weight	Kg. 3500

	DQ 1200 Wx
Electrical protection	Atex II2G IIA T3 to T2
Installed power	44,0 kW
Dimensions	cm 210 x 440 x 404 H
Weight	Kg. 3532



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 1200 Wx
--	------------------------

Loading capacity	1200 litres
Total volume of the boiler	2220 litres
Inner diameter of the boiler	1450 mm
Condensation unit	Stainless steel AISI 304
Cooling by	Water
Cover opening	pneumatic
Boiler tilting	by geared motor
Suitable for using Rec-Bags	no

Packing list for shipment		
Cardboard on pallet	cm 210 x 440 x 404 H	Kg. 3532



FORMECO

Company Certified UNI EN ISO 9001 : 2000

Distillation units series Industrial

Units composed by a boiler with pneumatic lifting of the cover and a separate box containing the control board electrical box, and all the other components making part of the plant. Units equipped with Pc-board, possibility to set a concentration (or dryness) cycle at the end of the distillation process, automatic loading for one or more consecutive cycles, regulation of the heating power, digital timers and thermostats, special pc-board with display for checking all the process parameters and setting different programs which can be memorised. Some optional: automatic unloading of the residue, automatic sending of the distillate to a remote service tank. Boiler equipped with scraping blades.



	SQ 2200 Wx
Electrical protection	AD-T
Installed power	60,0 kW
Dimensions	cm 230 x 600 x 410 H
Weight	Kg. 4000

	DQ 2200 Wx
Electrical protection	Atex II2G IIA T3 to T2
Installed power	60,0 kW
Dimensions	cm 230 x 600 x 410 H
Weight	Kg. 4032



FORMECO

Company Certified UNI EN ISO 9001 : 2000

	SQ / DQ 2200 Wx
--	------------------------

Loading capacity	2200 litres
Total volume of the boiler	3920 litres
Inner diameter of the boiler	1800 mm
Condensation unit	Stainless steel AISI 304
Cooling by	Water
Cover opening	pneumatic
Boiler tilting	by geared motor
Suitable for using Rec-Bags	no

Packing list for shipment		
Cardboard on pallet	cm 230 x 600 x 410 H	Kg. 4032